

USSN: 09/939,008

Docket No. 56760US008

Amendments to the Claims

A detailed list of all claims under examination is set out below. Please amend claims 79, 81, 82, 84 – 92, 94 – 101, 108, 110 – 112 and 114 (as shown below in marked form) and add new claim 146 (shown below):

Claims 1 – 38 (canceled).

39. (withdrawn): An electronic display structure comprising:
a display comprising a plastic substrate;
a first transparent layer of conductive barrier material deposited over the substrate, the conductive barrier material comprising a conductive oxide, metal or metal nitride; and
a first layer of organic polymer deposited contiguous to the first transparent layer.

40. (withdrawn): An electronic display structure comprising:
a display comprising a plastic substrate;
a first layer of organic polymer deposited over the substrate; and
a first transparent layer of conductive barrier material deposited contiguous to the first organic polymer layer, the conductive barrier material comprising a conductive oxide, metal or metal nitride.

Claims 41 – 49 cancelled.

50. (withdrawn): A process for fabricating a composite structure comprising:
providing a substrate;
depositing a first transparent layer of conductive barrier material over the substrate, the conductive barrier material comprising a conductive oxide, metal or metal nitride; and

USSN: 09/939,008

Docket No. 56760US008

depositing a first organic polymer layer contiguous to the first transparent layer;
wherein said composite structure comprises a display.

Claims 51 – 72 cancelled.

73. (withdrawn): The display structure of claim 39 wherein the display is between two dyads each comprising a layer of organic polymer material contiguous to a layer of conductive barrier material.

74. (withdrawn): The display structure of claim 73 further comprising one or more additional dyads comprising an additional transparent layer of conductive barrier material and a transparent layer comprising an organic polymer, a dielectric, a metal or a conductive oxide.

75. (withdrawn): The display structure of claim 40 wherein the display is between two dyads each comprising a layer of organic polymer material contiguous to a layer of conductive barrier material.

76. (withdrawn): The display structure of claim 75 further comprising one or more additional dyads comprising an additional transparent layer of conductive barrier material and a transparent layer comprising an organic polymer, a dielectric, a metal or a conductive oxide.

Claims 77 – 78 cancelled.

79. (currently amended): An electronic device on a plastic substrate, at least one side of the device being protected from reaction with or incorporation of moisture by coated with a composite barrier comprising one or more multiple layers of transparent conductive oxide separated by and one or more layers of organic dielectric polymer.

USSN: 09/939,008

Docket No. 56760US008

80. (previously presented): A device according to claim 79 wherein the transparent conductive oxide comprises an indium tin oxide.

81. (currently amended): A device according to claim 79 wherein the organic polymer comprises further comprising an acrylic hardcoat.

82. (currently amended): A device according to claim 79 wherein the composite barrier achieves at least about 50 a layer of the transparent conductive oxide has a sheet resistance less than 150 ohms/square and 85% visible transmittance.

83. (previously presented): A device according to claim 79 wherein the device comprises a light emissive device.

84. (currently amended): An electronic device on a substrate, comprising a water vapor-resistant barrier over at least one of the substrate or device, the barrier comprising in either order (a) a layer multiple layers of transparent conductive barrier material comprising conductive oxide, metal transparent metal, or transparent conductive metal nitride and (b) a nitride, separated by at least one layer of organic dielectric polymer.

85. (currently amended): A device according to claim 84 wherein the layer of transparent conductive barrier material is between the substrate or device and the layer a layer of organic polymer.

86. (currently amended): A device according to claim 84 wherein the layer claim 95 further comprising a layer of organic polymer is between between the substrate or device and the layer of transparent conductive barrier material first or second barrier, or over the first or second barrier.

USSN: 09/939,008

Docket No. 56760US008

87. (currently amended): A device according to claim 84 wherein the layer of ~~transparent conductive barrier material is comprises an amorphous layer~~.

88. (currently amended): A device according to claim 84 wherein the ~~transparent conductive barrier material is a comprises~~ conductive oxide.

89. (currently amended): A device according to claim 84 wherein the ~~transparent conductive barrier material comprises tin doped indium oxide~~.

90. (currently amended): A device according to claim 84 wherein the ~~transparent conductive barrier material comprises a cadmium one or more of cadmium oxide, tin oxide, indium oxide, zinc oxide or magnesium oxide, gallium-containing oxide, and magnesium oxide, which oxides may be doped~~.

91. (currently amended): A device according to claim 84 wherein the layer of ~~transparent conductive barrier material comprises an optically enhanced three layer configuration comprising adjacent layers of:~~

- a) ~~metal conductive oxide, metal, and or transparent conductive oxide;~~
- b) ~~conductive oxide, metal or metal nitride nitride, and conductive oxide; and~~
- c) ~~metal oxide or transparent conductive oxide nitride, metal, and metal nitride; or~~
- d) ~~conductive oxide, metal, and metal oxide~~

is substituted for one or more of the layers of transparent conductive oxide in the barrier.

92. (currently amended): A device according to claim 84 wherein the organic dielectric polymer is crosslinked.

93. (previously presented): A device according to claim 84 further comprising a hardcoat layer.

USSN: 09/939,008

Docket No. 56760US008

94. (currently amended): A device according to claim 84 comprising a layer of transparent conductive wherein the barrier material is between the substrate and the device.

95. (currently amended): A device according to claim 84 wherein the barrier device has at least two sides and comprises (a) a first layer of organic polymer over the substrate or device, barrier on a first side of the device comprising multiple layers of transparent conductive oxide, transparent metal, or transparent conductive metal nitride, separated by at least one layer of organic dielectric polymer, and (b) a first layer of transparent conductive material over the first layer of organic polymer and (c) a second layer of organic polymer over the first layer of transparent conductive barrier material on a second side of the device comprising multiple layers of transparent conductive oxide, transparent metal, or transparent conductive metal nitride, separated by at least one layer of organic dielectric polymer.

96. (currently amended): A device according to claim 95 wherein the first and second layers of organic dielectric polymer are crosslinked.

97. (currently amended): A device according to claim 95 whercin the first and second barriers further comprising comprise one or more pairs of a layer of organic dielectric polymer and a layer of transparent conductive oxide, transparent metal, or transparent conductive metal nitride barrier material and a layer of organic polymer, over the second layer of organic polymer.

98. (currently amended): A device according to claim 84 claim 95 further comprising at least one layer of transparent inorganic dielectric material.

99. (currently amended): A device according to claim 84 claim 98 comprising multiple pairs of layers of transparent barrier material and organic polymer wherein the inorganic dielectric material at least one of the layers of transparent barrier material comprises a metal oxide or metal nitride dielectric material.

USSN: 09/939,008

Docket No. 56760US008

100. (currently amended): A device according to claim 99 claim 79 wherein the device has at least two sides and there is at least one pair of layers of transparent material and organic polymer on each side of the device each of which is protected by the composite barrier.

101. (currently amended): A device according to claim 84 comprising one or more transparent metal layers between and one or more conductive or dielectric transparent metal nitride layers.

102. (withdrawn): A device according to claim 84 wherein the device comprises a plastic flat panel display.

103. (withdrawn): A device according to claim 84 wherein the device comprises a liquid crystal display.

104. (previously presented): A device according to claim 84 wherein the device comprises a light emitting device.

105. (previously presented): A device according to claim 84 wherein the device comprises an organic light emitting device.

106. (previously presented): A device according to claim 84 wherein the device comprises a field emission device.

107. (previously presented): A device according to claim 84 wherein the device comprises an electroluminescent device.

108. (currently amended): A device according to claim 84 wherein the substrate comprises a flexible plastic.

USSN: 09/939,008

Docket No. 56760US008

109. (withdrawn): A device according to claim 84 wherein the device comprises a flexible display.

110. (currently amended): A device according to claim 84 having an oxygen permeability less than ~~about 0.01 cc/m²*day~~ and a water vapor permeability less than ~~about 0.01 g/m²*day~~.

111. (currently amended): A device according to claim 84 having ~~an oxygen permeability less than about 0.001 cc/m²*day and a water vapor permeability less than about 0.001 g/m²*day~~.

112. (currently amended): A device according to claim 84 wherein the barrier excludes moisture and atmospheric gases that ~~chemically~~ degrade the performance of the device.

113. (previously presented): A device according to claim 84 wherein the barrier has low enough resistivity to function as an electrode for the device.

114. (currently amended): A device according to claim 84 comprising a plurality of electrodes of the transparent conductive wherein one or more of the barrier material layers is an electrode.

115. (withdrawn): A process for fabricating an oxygen- and water vapor-resistant electronic device comprising:

- a) providing an electronic device on a substrate; and
- b) depositing over the substrate or device a barrier comprising in either order (i) a coating comprising organic material and (ii) a coating comprising transparent conductive barrier material comprising conductive oxide, metal or conductive metal nitride.

USSN: 09/939,008

Docket No. 56760US008

116. (withdrawn): A process according to claim 115 wherein the coating comprising transparent conductive barrier material is deposited before the coating comprising organic material.

117. (withdrawn): A process according to claim 115 wherein the coating comprising organic material is deposited before the coating comprising transparent conductive barrier material.

118. (withdrawn): A process according to claim 115 wherein the transparent conductive barrier material is amorphous.

119. (withdrawn): A process according to claim 115 wherein the transparent conductive barrier material is a conductive oxide.

120. (withdrawn): A process according to claim 115 wherein the transparent conductive barrier material comprises tin doped indium oxide.

121. (withdrawn): A process according to claim 115 wherein the transparent conductive barrier material comprises a cadmium oxide, tin oxide, indium oxide, zinc oxide or magnesium oxide.

122. (withdrawn): A process according to claim 115 wherein the coating comprising transparent conductive barrier material is deposited as an optically enhanced three layer configuration comprising coatings of metal oxide or transparent conductive oxide; metal or metal nitride; and metal oxide or transparent conductive oxide.

123. (withdrawn): A process according to claim 115 wherein the coating comprising organic material is deposited as a monomer and crosslinked to form an organic polymer.

USSN: 09/939,008

Docket No. 56760US008

124. (withdrawn): A process according to claim 115 further comprising depositing a hardcoat on the substrate, device or previously deposited coatings.

125. (withdrawn): A process according to claim 115 comprising depositing a coating comprising transparent conductive barrier material so that the coating is between the substrate and the device.

126. (withdrawn): A process according to claim 115 comprising depositing (i) a first coating comprising organic material over the substrate or device, (ii) a first coating comprising transparent conductive barrier material over the first coating comprising organic material and (iii) a second coating comprising organic material over the first coating comprising transparent conductive barrier material.

127. (withdrawn): A process according to claim 126 wherein the first and second coatings comprising organic material are deposited as monomers and crosslinked to form organic polymers.

128. (withdrawn): A process according to claim 126 comprising depositing one or more pairs of a coating comprising transparent conductive barrier material and a coating comprising organic material, over the second coating comprising organic material.

129. (withdrawn): A process according to claim 115 further comprising depositing at least one coating comprising transparent dielectric material.

130. (withdrawn): A process according to claim 115 comprising depositing multiple pairs of a coating comprising transparent barrier material and a coating comprising organic material wherein the transparent barrier material of at least one of the pairs comprises a dielectric material.

USSN: 09/939,008

Docket No. 56760US008

131. (withdrawn): A process according to claim 130 wherein the device has at least two sides and at least one such pair is deposited on each side of the device.

132. (withdrawn): A process according to claim 115 wherein at least one coating comprising metal is deposited between coatings comprising metal nitride.

133. (withdrawn): A process according to claim 115 wherein the device comprises a plastic flat panel display.

134. (withdrawn): A process according to claim 115 wherein the device comprises a liquid crystal display.

135. (withdrawn): A process according to claim 115 wherein the device comprises a light emitting device.

136. (withdrawn): A process according to claim 115 wherein the device comprises an organic light emitting device.

137. (withdrawn): A process according to claim 115 wherein the device comprises a field emission device.

138. (withdrawn): A process according to claim 115 wherein the device comprises an electroluminescent device.

139. (withdrawn): A process according to claim 115 wherein the substrate comprises plastic.

140. (withdrawn): A process according to claim 115 wherein the device comprises a flexible display.

USSN: 09/939,008

Docket No. 56760US008

141. (withdrawn): A process according to claim 115 wherein the device has an oxygen permeability less than about 0.01 cc/m²*day and a water vapor permeability less than about 0.01 g/m²*day.

142. (withdrawn): A process according to claim 115 wherein the device has an oxygen permeability less than about 0.001 cc/m²*day and a water vapor permeability less than about 0.001 g/m²*day.

143. (withdrawn): A process according to claim 115 wherein the barrier excludes moisture and atmospheric gases that chemically degrade the performance of the device.

144. (withdrawn): A process according to claim 115 wherein the barrier has low enough resistivity to function as an electrode for the device.

145. (withdrawn): A process according to claim 115 comprising depositing a plurality of electrodes comprising the transparent conductive barrier material.

Please add the following new claim 146:

146. (new): A device according to claim 84 comprising a flexible light emitting device.